

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 January 2002 (17.01.2002)


PCT

(10) International Publication Number
WO 02/05583 A1

- (51) International Patent Classification⁷: **H04Q 7/32, H04L 12/56**
- (21) International Application Number: **PCT/GB01/02649**
- (22) International Filing Date: **14 June 2001 (14.06.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0016945.8 10 July 2000 (10.07.2000) GB
- (71) Applicant (for all designated States except US): **UBINET-ICS LIMITED** [GB/GB]; Cambridge Technology Centre, Melbourn, Cambridgeshire SG8 6DP (GB).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **LLOYD, Alex** [GB/GB]; 14 High Street, Hauxton, Cambridgeshire CB2 5HW (GB).
- (74) Agents: **PRATT, David, Martin et al.**; Withers & Rogers, Goldings House, 2 Hays House, London SE1 2HW (GB).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian**

[Continued on next page]

(54) Title: **MOBILE COMMUNICATIONS SYSTEM**



(57) Abstract: A communications system comprises a transceiver (2) for telecommunication with a remote base transceiver station of a mobile telecommunications network, and first and second SIM card holders (3, 4). Each holder (3, 4) is operatively associated with the transceiver (2) so that respective associated SIM cards can be simultaneously registered with the telecommunications network.



WO 02/05583 A1



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

MOBILE COMMUNICATIONS SYSTEM

This invention relates to a communications system, and in particular to a mobile telecommunications system.

A commercial mobile telecommunications service typically utilises a cellular network structure in which users communicate using mobile station terminal equipment (mobile handsets) and base transceiver stations located in the cells. In a modern system such as the GSM system (global system for mobile communications), each mobile handset contains a subscriber identity module (SIM). The SIM is a smart card, and has a computer memory chip permanently installed thereupon. The SIM is a crucial element of the GSM system, in that it contains user specific information such as the identity of the user (the telephone number of the user), information to ensure that calls are billed to the user, information to enable the user identity to be verified by the network, information to provide security invoice encryption, and telephone numbers saved as short dial codes that are specific to the user. The SIM can also be used to contain other information defined by the network. In fact, the SIM is the only part of a mobile telephone which is truly personal to the user. Conventionally, a SIM card is installed semi-permanently within the handset of a mobile phone.

The present invention provides a communications system comprising a transceiver for telecommunication with a remote base transceiver station of a mobile telecommunications network, and first and second SIM card holders, each of which is operatively associated with the transceiver so that respective associated SIM cards can simultaneously be registered with the telecommunications network.

Advantageously, the system further comprises first and second SIM cards positioned respectively in the first and second SIM card holders. In this fashion, the transceiver may handle calls for either of the two SIM cards, but obviously only one call can be in progress at a time.

In a preferred embodiment, the SIM card holders are physically connected to the transceiver. Alternatively, the SIM card holders are wirelessly connected to the transceiver, for example via Bluetooth transceivers.

- 5 In a preferred embodiment, the transceiver and a Bluetooth master unit are operatively associated in a first entity, the first SIM card holder and a first Bluetooth slave unit are operatively associated in a second entity, and the second SIM card holder and a second Bluetooth slave unit are operatively associated in a third entity.
- 10 Advantageously, the system further comprises one or more further entities, each of which has a further SIM card holder operatively associated with a further Bluetooth slave unit. In this way, a plurality of SIM cards may be simultaneously registered with the network via the single transceiver in the first entity, and each SIM card is able to make and receive calls, always subject to the limitation that no more than one call can
- 15 be in progress at a time.

Advantageously, each entity other than the first entity is provided with a battery, and preferably said each entity is provided with a microphone and a loudspeaker.

- 20 In a preferred embodiment, the transceiver of the first entity is provided with multiple instances of a TCP/IP protocol stack. Alternatively, the transceiver of the first entity is set up to use different ports from a single TCP/IP stack to multiplex/de-multiplex data from different users associated with each entity other than a first entity.
- 25 The invention will now be described in greater detail, by way of example, with reference to the drawing, the single figure of which is a schematic representation of a communications device constructed in accordance with the invention.

Referring to the drawing, a communications device 1 includes a GSM engine 2, first and second SIM card slots 3 and 4, a microphone 5, a loudspeaker 6, a keypad 7 and a display 8. The GSM engine 2 communicates with a base transceiver station (not shown) via an antenna 9. The GSM engine 2 is a GSM transceiver, and contains all the

30

functionality of a mobile phone handset apart from the items specifically mentioned above.

The communications device 1 described above could be mounted in a motor vehicle, in which case a first SIM card (not shown) could be semi-permanently installed by the user into the slot 3. A second SIM card (not shown) would, in this case, be semi-permanently installed in the slot 4 by, for example, the vehicle manufacturer or (where a motor vehicle is a leased vehicle) by the fleet manager. The second SIM card would allow a motor vehicle to report diagnostic information about the vehicle automatically without any input from the user. This SIM card would also allow communication between the vehicle and, say, the police in the event that the vehicle is stolen. Such information would allow the vehicle to be disabled or tracked by the police, thereby facilitating vehicle recovery. Both SIM cards are simultaneously registered with the telecommunications network, and the arrangement is such that either SIM card can make or receive calls. Obviously, if one of the SIM cards is in use, the other SIM card cannot be used until the call associated with said one SIM card is terminated.

The communications device 1 could also be configured as a mobile phone handset, in which case the two SIM cards could be used for different purposes. For example, the first SIM card could be used for business calls, and the second SIM card could be used for personal calls. In this case, the user's company would be charged for calls made by the first SIM card, and the user would be charged personally for calls made by the second SIM card. Another possibility would be for two members of the same family to use the same mobile phone handset, each having a respective SIM card for separate calling and charging purposes.

In a modified form of communications device (not shown) the SIM card slots 3 and 4 would be positioned a short distance away from the device, either together in a separate entity or as to two separate entities. In either case, a respective SIM card would be positioned in each of the slots 3 and 4, and each SIM card would communicate wirelessly with the communications device 1. For example, the communications

device 1 could be provided with a Bluetooth master unit, and a corresponding Bluetooth slave unit could be provided in the entity containing the two slots 3 and 4, or in each of the entities containing the separate SIM card slots.

5 Bluetooth is a computing and telecommunications industry specification that describes how mobile phones, computers and personal digital assistants (PDAs) can easily interconnect with each other and with home and business telephones using a short-range wireless connection. Each Bluetooth device is equipped with a microchip transceiver which transmits and receives in the previously-unused band of 2.45 GHz
10 that is available globally with some variation of bandwidth in different countries. In addition to data, up to three voice channels are available. Each Bluetooth device has a unique 48-bit address from the IEEE 802 standard, and connections can be point-to-point or multi-point. The maximum range of Bluetooth is 10 m, and data can be exchanged at a rate of 1 megabits per second (up to 2 Mbps in the second generation
--15 of the technology). A frequency hop scheme allows devices to communicate even in areas where is a great deal of electromagnetic interference. Built-in encryption and verification is provided in the Bluetooth specification.

Bluetooth provides a mechanism for creating short-range networks (piconets) which
20 dynamically change as users enter and leave the range of a Bluetooth master unit. Each piconet can support up to seven simultaneous devices (one master unit and six slave units)

In a further modification of this system, the communications device 1 could be used as
25 a GSM pay phone unit. In this case, users of the system would each be provided with a SIM entity which would incorporate a standard GSM SIM card connected to a Bluetooth slave unit. In this case, the communications device 1 (a GSM entity) would also include a Bluetooth master unit for communication with the Bluetooth slave unit of any SIM entity within the range of Bluetooth communications. Any such SIM entity
30 would be registered with the GSM network, though obviously only one of these entity could make or receive a call at any time. Each SIM entity would be provided with a small battery (either a primary cell or a rechargeable battery), a headset, (or a

microphone and a loudspeaker) a display and a keypad. A SIM entity could, therefore, be as cheap to manufacture as a simple pocket calculator.

- In order to make the system more vandalproof, the GSM pay phone unit could be located in a secure area, and need not be visible/accessible to the user. An advantage of this type of GSM pay phone system is that it is cheap to install. This would be particularly important in third world countries where it is often easier to roll-out a cellular network than to install a wired pay phone system. Normally, the cost of equipping the population with a large number of mobile phone handsets would be prohibitive in such third world countries. The use of the GSM pay phone system described above would, however, allow a rapid deployment of pay phone points which make use of a cellular infrastructure without complex investment in infrastructure (beyond the cellular infrastructure itself). Extremely low cost equipment could then be supplied to members of the population to enable them to make calls from the "pay phones". In this case, the use of pre-paid SIM cards would obviate billing problems. Another advantage of using this system in third world countries is that the GSM pay phone units themselves could be solar or battery powered, and so could be positioned practically anywhere.
- The system of the invention utilising a GSM entity and a plurality of SIM entities would permit multiple users of a general packet radio service (GPRS) to be registered with a single GSM engine, in such a manner that all may connect, for example, to the same wireless Internet provider. GPRS is a packet-based wireless communication service that permits continuous connection to the Internet for mobile phone and computer users. GPRS has the advantage of being cheaper than circuit-switched services, since communication channels are used on a shared-use, as-packets-are-needed basis rather than dedicated only to one user at a time. The system of the invention can be adapted for GPRS use by providing the GSM engine either with multiple instances of a TCP/IP protocol stack, or by using different ports from a single TCP/IP stack to multiplex/de-multiplex data from different users to the wireless IP provider. In this way, all the users can, for example, surf the web using a single GSM engine. The number of GPRS packets in either direction is managed by

6

the network in such a way that the total bandwidth remains within the capacity of the GSM engine and the network. In this way, multiple users can undertake packet data exchange on a GPRS enabled GSM engine, without any of the users being aware of the other users.

5


It will be apparent that the communications device described above provides additional functionality when compared with a standard mobile phone handset.

Claims

1. A communications system comprising a transceiver for telecommunication with a remote base transceiver station of a mobile telecommunications network, and
5 first and second SIM card holders, each of which is operatively associated with the transceiver so that respective associated SIM cards can be simultaneously registered with the telecommunications network.
2. A system as claimed in claim 1, further comprising first and second SIM cards
10 respectively positioned in the first and second SIM card holders.
3. A system as claimed in claim 1 or claim 2, wherein the SIM card holders are physically connected to the transceiver.
- 15 4. A system as claimed in claim 1 or claim 2, wherein the SIM card holders are wirelessly connected to the transceiver.
5. A system as claimed in claim 4, wherein the SIM card holders are connected to the transceiver via Bluetooth transceivers.
20
6. A system as claimed in claim 5, wherein the transceiver and a Bluetooth master unit are operatively associated in a first entity, the first SIM card holder and a first Bluetooth slave unit are operatively associated in a second entity and the second SIM card holder and a second Bluetooth slave unit are operatively associated in a third
25 entity.
7. A system as claimed in claim 6, further comprising one or more further entities, each of which has a further SIM card holder operatively associated with a further Bluetooth slave unit.
30
8. A system as claimed in claim 6 or claim 7, wherein each entity other than the first entity is provided with a battery.

9. A system as claimed in claim 8, wherein said each entity is provided with a display and a keypad.
10. A system as claimed in claim 8 or claim 9, wherein said each entity is provided with a microphone and a loudspeaker.
11. A system as claimed in any one of claims 6 to 10, wherein the transceiver of the first entity is provided with multiple instances of a TCP/IP protocol stack.
- 10 12. A system as claimed in any one of claims 6 to 10, wherein the transceiver of the first entity is set up to use different ports from a single TCP/IP stack to multiplex/de-multiplex data from different users associated with each entity other than the first entity.

1/1



INTERNATIONAL SEARCH REPORT

International Application No.

PC 176B 01/02649

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/32 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 198 23 074 A (ERICSSON TELEFON AB L M) 25 November 1999 (1999-11-25)	1-3
Y	column 5, line 2 - line 21	4-12
X	US 5 764 730 A (RABE DUANE C ET AL) 9 June 1998 (1998-06-09)	1-3
Y	column 6, line 3 - line 11 column 9, line 18 - line 44	4-12
Y	WO 00 11624 A (ERICSSON TELEFON AB L M) 2 March 2000 (2000-03-02) page 1, line 9 - line 11 page 3, line 16 -page 4, line 2	4-12
A	US 5 553 314 A (GRUBE GARY W ET AL) 3 September 1996 (1996-09-03) column 2, line 53 -column 3, line 23; figure 1	4-12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

24 October 2001

Date of mailing of the international search report

30/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Janyszek, J-M

INTERNATIONAL SEARCH REPORT

Inter: 1st Application No

PC170B 01/02649

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	HAARTSEN J: "BLUETOOTH - THE UNIVERSAL RADIO INTERFACE FOR AD HOC, WIRELESS CONNECTIVITY" ON - ERICSSON REVIEW, ERICSSON. STOCKHOLM, SE, no. 3, 1998, pages 110-117, XP000783249 ISSN: 0014-0171 the whole document	4-12
A	HOFF S ET AL: "A PERFORMANCE EVALUATION OF INTERNET ACCESS VIA THE GENERAL PACKET RADIO SERVICE OF GSM" VTC'98. 48TH. IEEE VEHICULAR TECHNOLOGY CONFERENCE. OTTAWA, CANADA, MAY 18 - 21, 1998, IEEE VEHICULAR TECHNOLOGY CONFERENCE, NEW YORK, NY: IEEE, US, vol. 3 CONF. 48, 18 May 1998 (1998-05-18), pages 1760-1764, XP000903322 ISBN: 0-7803-4321-2 paragraph '0IIC! paragraph '0III! paragraph '000V!	11,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC1/GB 01/02649

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19823074	A	25-11-1999	DE 19823074 A1	25-11-1999
			AU 4366699 A	13-12-1999
			WO 9962282 A1	02-12-1999
US 5764730	A	09-06-1998	AU 698138 B2	22-10-1998
			AU 3305595 A	18-04-1996
			BR 9504301 A	08-10-1995
			CA 2159766 A1	06-04-1996
			CN 1134096 A	23-10-1996
			ES 2112178 A1	16-03-1998
			FR 2725578 A1	12-04-1996
			GB 2293946 A, B	10-04-1996
			IT RM950658 A1	05-04-1996
			JP 8214367 A	20-08-1996
			KR 200261 B1	15-06-1999
			SG 33534 A1	18-10-1996
			ZA 9508408 A	08-05-1996
WO 0011624	A	02-03-2000	US 6250557 B1	26-06-2001
			AU 5767299 A	14-03-2000
			BR 9913470 A	05-06-2001
			CN 1313977 T	19-09-2001
			EP 1105852 A1	13-06-2001
			WO 0011624 A1	02-03-2000
US 5553314	A	03-09-1996	NONE	